


Item #	Part Number	Description
	MD401AS05	MP4H-DH (2 3/8" A.P.I. Reg. Pin)
1	MD401BH03	Backhead (2 3/8" A.P.I. Reg. Pin)
2	MD424OR01	O Ring
3	MB502CV02	Check Valve
4	MB503SP01	Spring
5	MD404SM01	Steel Make-Up Ring
6	MD405LR01	Lock Ring
7	MD407DR03	Air Distributor
8	MD421OR01	O Ring
9	MD422OR01	O Ring
10	MD409SR01	Seating Ring
11	MD408IC02	Inner Cylinder
12	MD410PN03	Piston
13	MD411WS04	Wear Sleeve
14	MD412PR01	Piston Retaining Ring
15	MD416BS01	Bit Retaining Spacer
16	MD413BR06	Bit Retaining Ring
17	MD420OR01	O Ring
18	MD414CK03	Chuck (DHD340A)
	MD426SK01	Service Kit
4	MB503SP01	Spring
	MD425OK01	O Ring Kit
	MD425OK01	O Ring Kit
	O Rings	O Rings for positions #2, #8, #9, #17

Specifications	Metric	Imperial
Hammer Outside Diameter	98 mm	3.86"
Shoulder to Shoulder	955 mm	37.6"
Backhead Spanner Flat Size	64 mm	2.5"
Drill Bit Shank Type	DHD340	
Minimum Bit Size	110 mm	4.3"
Hammer Weight (Less Bit)	38.5 kg	84.9 lbs
Drill Bit Weight	11.1 kg	24.5 lbs
Piston Weight	7.3 kg	16.1 lbs
Backhead Stand Off	0.75 mm	0.03"
Make up Torque	4,050-5,425 Nm	2,987-4,000 ft.lbf
Wear Sleeve Reverse Limit	Non-Reversible	
Wear Sleeve Discard Limit	87 mm	3.43"

Stated drill bit weight is indicative only. Actual drill bit weight will vary based on drill bit head size and carbide configuration.



Disclaimer:

1. Air consumption values are based on a combination of simulation data and real-world testing.
2. All air charts are based on normal temperature and atmospheric pressure: 20°C and 101.325 kPa (68°F and 14.696 psi).
3. Air density decreases with altitude, which will increase air consumption. Please consult the Mincon technical implementation team for exact air package requirements that take account for altitude and ground conditions.